

PACi Standard Cassettes

Product Code: S-50PU2E5A

5.0kW - PACi 4 Way Cassette Indoor Unit - Split - R410A

Notes

- » New high performance turbo fan, new path system for heat exchanger
- » Lower noise in slow fan operation
- » Light weight, easy piping
- » Easy installation structure of the panel
- » Econavi: Floor temperature and humidity sensor added.
- » Nanoe»: The first 10x for CAC (10 times more purification power)



MODEL NUMBER		S-50PU2E5A
GRILLE		CZ-KPU3
Nominal cooling	kW	5
Nominal heating	kW	5.6
Height	mm	256 (33,5)
Width	mm	840 (950)
Depth	mm	840 (950)
Weight	kg	20 (5)
Knock out for fresh air intake		Yes (100mm diameter)
Knock out for branch duct		TBC
Indoor unit airflow rate (l-h)	l/s	192 - 225 - 275 (L - M - H)
Moisture Removal Volume	l/h	1.6
Static pressure	pa	NA
Spigot Kit		NA
Discharge spigot		NA
Sound pressure level (l-m-h)	dB(A)	27 - 29 - 32
Pipe connection size - gas	in	1/2"
Pipe connection size - liquid	in	1/4"
Refrigerant		R410A
Drain connection	mm	VP25 (32mm OD)
Lift pump?		Yes (850mm)
Power supply	V-Ph-Hz	230-1-50
Interconnecting cables		2 core
Suggested fuse size		5
Controller included?		No

* exact cooling and heating capacities will depending on connected outdoor unit and system configuration

